



## EPDM Flächenkleber SprayBond

**Safety data sheet** According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** EPDM Flächenkleber SprayBond  
**UFI** T6J0-D0V0-600Q-4S2S  
**Container Size** 750 ml  
**REACH registration notes** All chemicals used in this product have been registered under REACH where required.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses**

Adhesive.

**Uses advised against**

Flexible PVC due to the risk of plasticiser migration.

#### 1.3 Details of the supplier of the safety data sheet

**Supplier:**

Hanse Baustoffe Handelsges. mbH & Co. KG  
Lily-Braun-Str. 46  
23843 Bad Oldesloe  
Germany  
Tel.: +494531 8882244  
Fax: +494531 8882240  
E-Mail: info@hanse-baustoffe.de  
www.hanse-baustoffe.de

#### 1.4 Emergency telephone number

Poison Hotline Berlin Charité: +4930 30686700 (Consultation in German and English),  
Area of application Germany and Austria

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (EC 1272/2008)**

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 2 - H411

#### 2.2 Label elements

**Pictogram**



**Signal word**

Danger

**Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.



### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with national regulations.

### Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.  
Please refer to Safety Data Sheet.

### Contains

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane, PENTANE, ACETONE

### Supplementary precautionary statements

P261 Avoid breathing vapour/spray.  
P264 Wash contaminated skin thoroughly after handling.  
P273 Avoid release to the environment.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P405 Store locked up.

### 2.3 Other hazards

Containers should be thoroughly emptied before disposal because of the risk of an explosion. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. In use may form flammable/explosive vapour-air mixture. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

<b>DIMETHYLETHER</b> CAS number: 115-10-6	EC number: 204-065-8	REACH registration number: 01-2119472128-37-XXXX	<b>30-60%</b>
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas (Liq.) - H280			
<b>Hydrocarbons, C6-C7, isoalkanes, cyclics, &lt;5% n-hexane</b> CAS number: ---	EC number: 926-605-8	REACH registration number: 01-2119486291-36-0000	<b>10-30%</b>
<b>Classification</b> Flam. Liq. 2 - H225 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			



<b>PENTANE</b> CAS number: 109-66-0	EC number: 203-692-4	REACH registration number: 01-2119459286-30-0000	<b>10-30%</b>
<b>Classification</b> Flam. Liq. 1 - H224 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
<b>ACETONE</b> CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX	<b>1-5%</b>
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1 Description of first aid measures

###### General information

Move affected person to fresh air at once. Show this Safety Data Sheet to the medical personnel.

###### Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. If breathing stops, provide artificial respiration. Get medical attention immediately.

###### Ingestion

Rinse mouth thoroughly with water. Get medical attention. Do not induce vomiting.

###### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

###### Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. If adhesive bonding occurs, do not force eyelids apart.

###### Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue.

##### 4.2 Most important symptoms and effects, both acute and delayed

###### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

###### Inhalation

Coughing, chest tightness, feeling of chest pressure. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

###### Ingestion

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

###### Skin contact

Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin.

###### Eye contact

Irritating to eyes. Profuse watering of the eyes.



#### **4.3 Indication of any immediate medical attention and special treatment needed**

##### **Notes for the doctor**

Show this Safety Data Sheet to the medical personnel.

##### **Specific treatments**

If adhesive bonding occurs, do not force eyelids apart.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

Water spray, dry powder or carbon dioxide. Alcohol-resistant foam.

##### **Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

#### **5.2 Special hazards arising from the substance or mixture**

##### **Specific hazards**

Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Bursting aerosol containers may be propelled from a fire at high speed.

##### **Hazardous combustion products**

Oxides of carbon. Acrid smoke or fumes.

#### **5.3 Advice for firefighters**

##### **Protective actions during firefighting**

Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control runoff water by containing and keeping it out of sewers and watercourses.

##### **Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

##### **Personal precautions**

Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not breathe vapour. Avoid contact with eyes and prolonged skin contact.

##### **For non-emergency personnel**

For the greatest protection, clothing should include anti-static overalls, boots and gloves.

##### **For emergency responders**

For the greatest protection, clothing should include anti-static overalls, boots and gloves.

#### **6.2 Environmental precautions**

##### **Environmental precautions**

Contain spillage with sand, earth or other suitable non-combustible material.

#### **6.3 Methods and material for containment and cleaning up**

##### **Methods for cleaning up**

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools.

#### **6.4 Reference to other sections**

##### **Reference to other sections**

For personal protection, see Section 8. For waste disposal, see Section 13.



## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Usage precautions

Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Wear protective clothing as described in Section 8 of this safety data sheet. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.

#### Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage precautions

Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from the following materials: Alkalis.

#### Storage class

Extremely Flammable Aerosol

### 7.3 Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

##### DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m<sup>3</sup>

##### PENTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1800 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

##### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

#### DIMETHYLETHER (CAS: 115-10-6)

- PNEC**
- Fresh water; 0,155 mg/l
  - Intermittent release, Water; 1,549 mg/l
  - Water; 160 mg/l
  - marine water; 0,016 mg/l
  - Sediment (Freshwater); 0,681 mg/l
  - Sediment (Marinewater); 0,069 mg/l
  - Soil; 0,045 mg/l

#### PENTANE (CAS: 109-66-0)

- DNEL**
- Industry - Dermal; Long term systemic effects: 432 mg/kg/day
  - Industry - Inhalation; Long term systemic effects: 3 mg/m<sup>3</sup>
  - Consumer - Dermal; Long term systemic effects: 214 mg/kg/day



Consumer - Inhalation; Long term systemic effects: 643 mg/m<sup>3</sup>  
Consumer - Oral; Long term systemic effects: 214 mg/kg/day

**ACETONE (CAS: 67-64-1)**

<b>DNEL</b>	Consumer - Oral; Long term : 62 mg/kg/day Consumer - Dermal; Long term : 62 mg/kg/day Industry - Dermal; Long term : 186 mg/kg/day Consumer - Inhalation; Long term : 200 mg/m <sup>3</sup> Industry - Inhalation; Short term : 2420 mg/m <sup>3</sup> Industry - Inhalation; Long term : 1210
<b>PNEC</b>	- Fresh water; 10.6 mg/l - marine water; 1.06 mg/l - Intermittent release; 21 mg/l - Soil; 29.5 mg/l - Sediment (Marinewater); 3.04 mg/kg - Sediment (Freshwater); 30.4 mg/kg

## 8.2 Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

### Personal protection

Wear protective clothing.

### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

### Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. (PE/PA/PE), 2.5mil (0.06mm), >480 min. Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

### Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

### Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.

### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Short term Gas filter, type AX.



#### Thermal hazards

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

#### Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Amber.
<b>Odour</b>	Acetone. Ketonic. Hydrocarbons.
<b>Odour threshold</b>	Data lacking.
<b>pH</b>	pH (concentrated solution): 7
<b>Melting point</b>	Data lacking.
<b>Initial boiling point and range</b>	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane: 75-93°C Pentane: 35-37°C Acetone: 55.8-56.6°C
<b>Flash point</b>	A flash point method is not available for aerosols, but the major hazardous component, the propellant (Dimethyl ether) has a flash point of <-41°C with flammability limits of 3.3% vol. upper and 26.2% vol. lower.
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	No specific test data are available.
<b>Other flammability</b>	No specific test data are available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Liquid base: 0.83 @ 20°C
<b>Bulk density</b>	Not applicable.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	No information available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Liquid base: 280-480 cP @ 20°C
<b>Explosive properties</b>	In use may form flammable/explosive vapour-air mixture.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

#### 9.2 Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 578 g/l.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

##### Reactivity

Under normal conditions of storage and use, no hazardous reactions will occur.

#### 10.2 Chemical stability

##### Stability

Stable at normal ambient temperatures and when used as recommended. Highly volatile.

#### 10.3 Possibility of hazardous reactions

##### Possibility of hazardous reactions

Will not polymerise. In use may form flammable/explosive vapour-air mixture.

#### 10.4 Conditions to avoid

##### Conditions to avoid

Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.



## 10.5 Incompatible materials

### Materials to avoid

Strong acids. Strong oxidising agents. Strong alkalis.

## 10.6 Hazardous decomposition products

### Hazardous decomposition products

Oxides of carbon.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** May cause drowsiness or dizziness.

#### Aspiration hazard

**Aspiration hazard** Not relevant.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Route of exposure** Inhalation Skin absorption

**Target organs** Central nervous system Respiratory system, lungs Skin

**Medical symptoms** Narcotic effect. Vapours may cause drowsiness and dizziness.

#### Toxicological information on ingredients.

#### **DIMETHYLETHER**

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Not applicable.

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Not applicable.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** 164000 ppm, Inhalation, Rat

##### Skin corrosion/irritation

**Skin corrosion/irritation** Based on available data the classification criteria are not met.

##### Serious eye damage/irritation

**Serious eye damage/irritation**

Based on available data the classification criteria are not met.

##### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

##### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

##### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

##### Reproductive toxicity

**Reproductive toxicity - fertility**

This substance has no evidence of toxicity to reproduction.





**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Based on available data the classification criteria are not met.

**Skin contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Medical symptoms** Symptoms following overexposure may include the following:  
Arrhythmia (deviation from normal heart beat).

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**

**Skin corrosion/irritation**

**Skin corrosion/irritation** Irritating to skin.

**Serious eye damage/irritation**

**Serious eye damage/irritation**

Based on available data the classification criteria are not met.

**Respiratory sensitisation**

**Respiratory sensitisation** Based on available data the classification criteria are not met.

**Reproductive toxicity**

**Reproductive toxicity - fertility**

Based on available data the classification criteria are not met.

**General information**

The product irritates mucous membranes and may cause abdominal discomfort if swallowed.

**PENTANE**

**Acute toxicity - oral**

**Acute toxicity oral** 2.0

**(LD<sub>50</sub> mg/kg)**

**Species** Rat

**Acute toxicity - inhalation**

**Acute toxicity inhalation** 25.3

**(LC<sub>50</sub> vapours mg/l)**

**Species** Rat

**ATE inhalation** 25.3

**(vapours mg/l)**

**Respiratory sensitisation**

**Respiratory sensitisation** Based on available data the classification criteria are not met.

**Skin sensitisation**

**Skin sensitisation** Based on available data the classification criteria are not met.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

**Carcinogenicity**

**Carcinogenicity** Based on available data the classification criteria are not met.

**Reproductive toxicity**

**Reproductive toxicity - fertility**

Based on available data the classification criteria are not met.

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Based on available data the classification criteria are not met.

**Aspiration hazard**

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** May cause discomfort.



#### ACETONE

<b>Toxicological effects</b>	The toxicity of this substance has been assessed during REACH registration.
<b><u>Acute toxicity - dermal</u></b>	
<b>Acute toxicity dermal (LD<sub>50</sub> mg/kg)</b>	2,000.0
<b>Species</b>	Rabbit
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Epidemiological studies have shown no evidence of skin sensitisation.
<b>Skin contact</b>	Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.

### SECTION 12: Ecological information

#### Ecotoxicity

The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

#### Ecological information on ingredients.

##### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

<b>Ecotoxicity</b>	Toxic to aquatic life with long lasting effects.
--------------------	--

#### 12.1 Toxicity

#### Ecological information on ingredients.

##### DIMETHYL ETHER

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: >4000 mg/l, Poecilia reticulata (Guppy)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: >4000 mg/l, Daphnia magna LC <sub>50</sub> , 48 hours: 755,549 mg/l, Daphnia magna

##### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LL <sub>50</sub> , 96 hours: 9.776 mg/l, Freshwater fish
<b>Acute toxicity - aquatic invertebrates</b>	EL50, 48 hours: 3.0 mg/l, Daphnia magna
<b>Acute toxicity - microorganisms</b>	NOEL, 48 hours: 8.483 mg/l, Tetrahymena pyriformis.

##### PENTANE

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 4.26 mg/l, Oncorhynchus mykiss (Rainbow trout)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 2.7 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	NOEC, 72 hours: 7.51 mg/l, Freshwater algae EC <sub>50</sub> , 72 hours: 10.7 mg/l, Freshwater algae

##### ACETONE

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: >100 mg/l, Fish
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 12600 mg/l, Daphnia magna EC <sub>50</sub> , 48 hours: 8300 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	IC <sub>50</sub> , 72 hours: >100 mg/l, Algae



**Chronic aquatic toxicity**

**Chronic toxicity - aquatic** NOEC, 28 days: >10<100 mg/l, Freshwater invertebrates  
Invertebrates

**12.2 Persistence and degradability**

**Persistence and degradability**

Biodegradable in part only.

**Ecological information on ingredients.**

**DIMETHYL ETHER**

**Persistence and degradability**

Not readily biodegradable.

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**

**Persistence and degradability**

The product is biodegradable.

**PENTANE**

**Persistence and degradability**

The product is biodegradable. Volatile substances are degraded in the atmosphere within a few days.

**ACETONE**

**Persistence and degradability**

The product is readily biodegradable.

**12.3 Bioaccumulative potential**

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

**Ecological information on ingredients.**

**DIMETHYL ETHER**

**Bioaccumulative potential** No data available on bioaccumulation.

**PENTANE**

**Bioaccumulative potential** Not determined.

**12.4 Mobility in soil**

**Ecological information on ingredients.**

**DIMETHYL ETHER**

**Mobility** Koc: 7,759

**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**PENTANE**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

**12.5 Results of PBT and vPvB assessment**

**Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

**Ecological information on ingredients.**

**DIMETHYL ETHER**

**Results of PBT and vPvB assessment**

This substance is not classified as PBT or vPvB according to current EU criteria.



**Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**

**Results of PBT and vPvB assessment**

This substance is not classified as PBT or vPvB according to current EU criteria.

**PENTANE**

**Results of PBT and vPvB assessment**

This substance is not classified as PBT or vPvB according to current EU criteria.

**ACETONE**

**Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

**12.6 Other adverse effects**

**Other adverse effects**

Not available.

**Ecological information on ingredients.**

**PENTANE**

**Other adverse effects**

None known.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Disposal methods**

Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or water-courses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

**Waste class**

Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

**SECTION 14: Transport information**

**14.1 UN-Number**

<b>UN No. (ADR/RID)</b>	1950
<b>UN No. (IMDG)</b>	1950
<b>UN No. (ICAO)</b>	1950
<b>UN No. (ADN)</b>	1950

**14.2 UN proper shipping name**

<b>Proper shipping name (ADR/RID)</b>	AEROSOLS
<b>Proper shipping name (IMDG)</b>	AEROSOLS
<b>Proper shipping name (ICAO)</b>	AEROSOLS
<b>Proper shipping name (ADN)</b>	AEROSOLS

**14.3 Transport hazard class(es)**

<b>ADR/RID class</b>	2.1
<b>ADR/RID classification code</b>	5F
<b>ADR/RID label</b>	2.1
<b>IMDG class</b>	2.1
<b>ICAO class/division</b>	2.1
<b>ADN class</b>	2.1



#### Transport labels



#### 14.4 Packaging group

Not applicable.

#### 14.5 Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6 Special precautions for user

IMDG Code segregation group	SG69
EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).  
Health and Safety at Work etc. Act 1974 (as amended).  
Control of Substances Hazardous to Health Regulations 2002 (as amended).

##### EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

##### Guidance

Workplace Exposure Limits EH40.

##### Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

##### Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

#### 15.2 Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

#### Classification procedures according to Regulation (EC) 1272/2008

Aerosol 1 - H222, H229: Weight of evidence. STOT SE 3 - H336, Aquatic Chronic 2 - H411: Calculation method.

Revision date 25/07/2018

Revision 4

Supersedes date 21/03/2018

#### Hazard statements in full

H220 Extremely flammable gas.



H222 Extremely flammable aerosol.  
H224 Extremely flammable liquid and vapour.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.